

MATERIAL SAFETY DATA SHEET



1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

Name: **TRACKCRETE.**
Application: As a fast setting concrete
Company: **Natural Cement Distribution Ltd.,**
Address 15 Fountain Parade, Off Spark Lane, Mapplewell, Barnsley. S75 6FW
Telephone 01226 381133/381155 Fax 01226 381177 www.naturalcement.co.uk

2: COMPOSITION AND INFORMATION ON INGREDIENTS

Composition **TRACKCRETE** is a mix of natural cement based binder and aggregates. By its nature, it can vary slightly in composition. Like Artificial Portland Cements it is composed of Calcium Aluminates and Silicates, with small Quantities of Lime and Magnesium, plus sulphates of Sodium, potassium and Calcium.

3: HAZARDS IDENTIFICATION

As Powder	Irritant (XI).	TRACKCRETE contains a very fine powder. It should not be allowed to come into contact with the eyes. Risk Phrases R36, R37, R36
During Hydration	Irritant (XI).	As with all cements, TRACKCRETE releases a strong alkali when it comes into contact with water (Hydration), including the mucous membranes of the nose, mouth and eyes. This alkali may occasionally cause burns or irritation. There is a possibility of an allergic reaction in hypersensitive individuals to salts of trace elements Chromium, formed during Hydration. Risk Phrases R41, R43. Avoid prolonged contact with wet Paste, Mortar or Concrete. Upon Hydration (After Mixing with water) a little heat is released. This is not a dangerous level.

4: FIRST AID

As Powder	Eye Contact	Irrigate immediately and profusely with clean water, to eliminate all trace of the powder.
	Skin Contact	Wash immediately and profusely with Soap and Water.
	Inhalation	Remove subject into fresh air until symptoms subside.
	Ingestion	Give plenty of water to drink. If symptoms persist, seek medical attention.
	As Hydrated Cement	In the event of a burn or irritation, wash the area thoroughly with cold water and seek medical advice.

5: FIRE FIGHTING MEASURES

TRACKCRETE is not flammable. (UN. Class MO), nor will it facilitate the combustion of other materials.

6: ACCIDENTAL RELEASE

As powder Measures

Avoid Breathing the powder or dust.

Clean up powder spillage with brush or vacuum cleaner, taking care not to raise excessive dust.

As hydrated

Allow to set before cleaning up cement

7: HANDLING & STORAGE

Packing

TRACKCRETE is normally packed in a polythene bag within a stitch sealed woven polypropylene outer sack.

Safety

Avoid spillage from broken bags.

Avoid raising dust while sweeping.

Wear suitable protective clothing when handling bags, which may have small amounts of material on the outside.

Storage

Store in dry conditions.

8: EXPOSURE CONTROL

As powder

No specific data is available, but exposure tolerances would be greater than those for Portland Cement: 10mg/M3 total inhalable dust, 5mg/M3 respirable dust. 8 Hr TWA

Personal Protection

Avoid breathing the powder

Avoid raising dust

WEAR SAFETY GOGGLES, WORK GLOVES and DUST MASK

When Mixing

Always add the powder to the water in order to avoid raising dust.

WEAR SAFETY GOGGLES, DUST MASK and WATERPROOF GLOVES

When Working

Discard immediately any clothing that becomes saturated with wet cement.

Avoid contact with the wet mortar, concrete or grout during the setting reaction. **WEAR WATERPROOF GLOVES.** Discard immediately any clothing that becomes saturated with wet cement.

9: PHYSICAL AND CHEMICAL

Appearance	Beige Grey Powder
Ph value	12 to 13 in water
Apparent Density	1.0
True	2.7
Solubility in water.	The dissolution is accompanied by the precipitation of the hydrates formed, i.e. On contact with water TRACKCRETE part dissolves, combines with the water and sets hard. Setting Time is 35 mins at 20°C.

10: STABILITY AND REACTIVITY

TRACKCRETE	Is stable and inert when set, and as a DRY powder
-------------------	---

11: TOXICOLOGY INFORMATION

TRACKCRETE	Is not toxic. In the case of prolonged contact while setting, TRACKCRETE can cause desiccation of the skin and/or mucous membranes. When the setting reaction is occurring, certain salts of trace (e.g. Chromium) can cause an allergic reaction to the skin of certain individuals after long or repeated contact.
-------------------	---

12: ECOLOGICAL INFORMATION

Manufacture	TRACKCRETE is manufactured in plant equipped with filters preventing emission of dust to the atmosphere. TRACKCRETE is transported pneumatically within the plant to avoid dust emissions.
In use	After setting and hardening, TRACKCRETE concretes are insoluble and stable.

13: DISPOSAL CONSIDERATIONS

As Powder	Unused TRACKCRETE should be set with water before disposal.
As Paste, Mortar or Concrete.	Once set TRACKCRETE is inert, non-toxic, non-biodegradable, and will not affect drinking water.
General	Disposal should always comply with local, National and/or EC regulations.

14: TRANSPORT INFORMATION

TRACKCRETE

Requires no special precautions.

15: REGULATORY INFORMATION

TRACKCRETE

Is not subject to regulatory legislation.

This SAFETY DATA SHEET supplements, but does not replace, other information given regarding the use of **TRACKCRETE**.

The user bears the responsibility to ensure that **TRACKCRETE** is used only in accordance with our instructions for the purposes intended.

Risk Phrases applicable to the powder.

R36 Irritant to Eyes.

R37 Instant to Respiratory System.

R38 Irritant to Skin.

Risk Phrases applicable during hydration

R41 Risk of serious damage to Eyes.

R43 May cause sensitisation by skin contact.

Safety Phrases

S2 Keep out of reach of Children

S22 Do not breath dust.

S24 Avoid contact with skin.

S26 In case of contact with Eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of soap and water.

S36 Wear suitable protective clothing

S37 Wear Suitable Clothing

S39 Wear eye and face protection.

16: OTHER INFORMATION

Further advice and information regarding the handling of cement products generally is available from:-

Natural Cement Distribution Ltd

15 Fountain Parade Mapplewell Barnsley S75 6FW

TEL: 01226 381133

Fax: 01226 381177

www.naturalcement.co.uk

H. S. E. Construction Information Sheet No- 26 (Cement) Revision 2
Health and Safety at Work Act 1974 Control of Substances Hazardous to Health (Regulations) 1999
Portland Cement Dust - Criteria Document for an Occupational Exposure Limit. H.S.E. Guidance Note EH 57/7
H.S.E. Leaflet MS(B)G
H.S.E. Guidance Note EH40 (Exposure Limits)
Manual Handling Operations Regulations 2002
Chemicals (Hazard Information and Packaging) Regulations 1993

This SAFETY DATA SHEET is compiled in the full state of our current knowledge of the product in January 2011, and is subject to revision without notice. Users should ensure that they are aware of the latest revisions.